

Appl. No. 09/816,644
Amdt. Dated May 17, 2004
Reply to Office Action of January 16, 2004

Attorney Docket No. 81784.0229
Customer No.: 26021

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended): An error detection and correction circuit for detecting and correcting an error in an input signal containing a first signal and a second signal, comprising:

a selection circuit for selecting either the first signal or the second signal in the input signal;

an error detection and correction unit for detecting and correcting an error in an output signal from the selection circuit; ~~and~~

a switch circuit for outputting an output signal from the error detection and correction unit to either an output path for the first signal or an output path for the second signal; and

a memory;

and wherein the selection circuit selects the second signal and sends the second signal to the memory;

the memory stores the second signal until an amount of the stored second signal becomes a predetermined amount; and

the error detection and correction unit receives the predetermined amount of the second signal where the amount of the second signal in the memory becomes the predetermined amount.

2. (Currently Amended): An error detection and correction device according to claim 1, wherein

the error detection and correction unit ~~has a~~ includes the memory ~~storing,~~
and the memory stores the first signal and the second signal.

3. (Original): An error detection and correction device according to claim 2, wherein the memory has a first predetermined area storing the first signal and a second predetermined area storing the second signal.

4. (Currently Amended): An error detection and correction device according to claim 1, wherein

the error detection and correction unit receives the first signal when the first signal is supplied, and conducts error correction to the first signal received, and

the error detection and correction unit receives the second signal when the second signal is supplied, and conducts error correction to the ~~first~~ second signal received.

5. (Original): An error detection and correction device according to claim 1, wherein the first signal occupies a larger portion of the input signal than the second signal.

6. (Original): An error detection and correction device according to claim 1, wherein the first signal is a main signal and the second signal is a TMCC signal, and wherein both are present in a received signal for satellite digital television broadcasting.

7. (Currently Amended): ~~An error detection and correction device according to claim 1,~~ An error detection and correction circuit for detecting and

correcting an error in an input signal containing a first signal and a second signal, comprising:

a selection circuit for selecting either the first signal or the second signal in the input signal;

an error detection and correction unit for detecting and correcting an error in an output signal from the selection circuit; and

a switch circuit for outputting an output signal from the error detection and correction unit to either an output path for the first signal or an output path for the second signal; wherein

the error detection and correction signal sets a completion flag upon completion of error detection and correction with respect to the first signal received, and

the selection circuit supplies the second signal to the error detection and correction unit when the selection circuit receives the second signal and detects the completion flag.

8. (Original): An error detection and correction device according to claim 7, wherein

the error detection and correction unit calculates a syndrome based on the input signal, processes the syndrome calculated to calculate an error position polynomial and an erroneous value polynomial, and conducts error correction based on the error position polynomial calculated and the erroneous value polynomial calculated, and

the error detection and correction unit sets the completion flag upon completion of calculation of an error position polynomial and an erroneous value polynomial with respect to the first signal.

9. (Original): An error detection and correction device according to claim 7, wherein the first signal occupies a larger portion of the input signal than does the second signal.

10. (Original): An error detection and correction device according to claim 9, wherein the selection circuit supplies the second signal to the error detection and correction unit when the selection circuit receives a predetermined number of second signals and detects the completion flag set.

11. (Original): An error detection and correction device according to claim 9, wherein the first signal is a main signal and the second signal is a TMCC signal, and wherein both are present in a received signal for satellite digital television broadcasting.